



For the following igus® series

E2.1

● E2.48

E2/000

● 3500

For 1m trough without glide bars
6 tubes 1m long are required.
For 1m trough with glide bars 4
tubes 1m long are required.

Tubular trough | Components

Individual parts	Part No.	Weight
Installation set without glide bars	93.70.XXX	≈ 0.25kg
Installation set with glide bars	93.71.XXX	≈ 0.20kg
Installation set junction	93.74.XXX	
Fastening set	92.77.2	
Tubular steel, diameter ø 15 x 1 galvanised	93.80	≈ 0.50kg

(L = 985) for clearance Installation set 1m)

Installation dimensions

XXX	Bi	Ba	B _{Ra}	B _{Ri}
050	50	70	130	75
075	75	95	155	100
100	100	120	180	125
115	115	135	195	140
125	125	145	205	150
150	150	170	230	175
175	175	195	255	200
200	200	220	280	225
225	225	245	305	250
250	250	270	330	275

Please add the width index **XXX**. Example: 93.71.050

XXX = Width index



Order example: e-chain® inner width 50mm.

For 8m trough the following parts are required:

Area with glide bar:	4 x installation set +	93.71.050
	tube: 4 x 4 piece	93.80
Area without glide bar	4 x installation set +	93.70.050
	Tube: 4 x 6 piece	93.80
Transition from area without glide bar to area with glide bar	1 x installation set junction	93.74.050